

VBLOK SG-1 Spray Gun

Category: Application

Technical Data Sheet

The **SG-1** spray application tool is a 1 quart, internal mix, siphon feed spray gun designed to deliver high solids vibration damping and thermal control coatings. The **SG-1** features an aluminum, 1 quart cup and 0.5" interior diameter draw tube to ensure maximum material flow. Additional features include delivery rate adjustment, a press forged brass handle and 0.250" nozzle opening. The spray pattern is conical with a heavy particle spray. The result is product where you need it with minimal overspray.



Benefits:

- □ Easy to use
- □ Cost effective alternative to expensive spray guns
- □ Lightweight, durable construction
- □ Cleans up easily with warm water
- □ Heavy spray pattern with minimal overspray
- Adjustable Delivery Rate

Applications:

- □ Automotive body panels
- □ Loudspeaker enclosures
- □ Industrial hoppers, chutes, ducting

Specifications:

| Body/Container |
|----------------------------------|
| Color |
| Net Weight (Empty) |
| Tank Capacity |
| Recommended Working Air Pressure |

Press-Forged Brass and Aluminum Aluminum/Silver 1.6 lbs. 1 US Quart 60 - 80 PSI



VB-1X and TG-1 Installation Instructions Available at www.cascadeaudio.com

Cascade Audio Engineering - PH: 541-389-6821 - FX: 541-389-5273 - sales@cascadeaudio.com - www.cascadeaudio.com